



Apple

9L0-008

**Apple Macintosh
Service Certification
Exam**

Version: Demo

[Total Questions: 10]

Web: www.exams4sure.com

Email: support@exams4sure.com

IMPORTANT NOTICE

Feedback

We have developed quality product and state-of-art service to ensure our customers interest. If you have any suggestions, please feel free to contact us at feedback@exams4sure.com

Support

If you have any questions about our product, please provide the following items:

- ▶ exam code
- ▶ screenshot of the question
- ▶ login id/email

please contact us at support@exams4sure.com and our technical experts will provide support within 24 hours.

Copyright

The product of each order has its own encryption code, so you should use it independently. Any unauthorized changes will inflict legal punishment. We reserve the right of final explanation for this statement.

Question #:1

You require additional information about a specific problem with a customer's Mac. Which one of the following resources is the Apple-recommended choice for researching the problem?

- A. Downloads
- B. Discussions
- C. User's manual
- D. Knowledge Base

Answer: D

Question #:2

A MacBook sometimes becomes unresponsive and the cursor freezes on the display when running an application. You have verified the symptom, and have already attempted to force the application to quit, but the computer remains unresponsive. What should you try next?

- A. Disconnect all power sources for several minutes to reset the SMC.
- B. Hold the eject button down for several seconds to reset the application.
- C. Hold the trackpad button down for several seconds to regain cursor control.
- D. Press the power button for several seconds to try shutting the computer down.

Answer: D

Question #:3

What precautions should be taken if a discharged CRT must remain exposed for any length of time?

- A. You should reset the Power Manager Unit on the logic board.
- B. You should perform a full set of video adjustments on the CRT.
- C. You should remove the CRT from the computer or display assembly.
- D. You should establish an ongoing lead between the CRT anode and ground.

Answer: D

Question #:4

Which of the following most accurately describes what happens during Safe Sleep activation in Mac portables?

- A. The contents of RAM are written to NVRAM before sleep.
- B. The contents of the hard disk are encrypted before sleep.
- C. The contents of RAM are written to hard disk before sleep.
- D. The contents of the hard disk are read into RAM before sleep.

Answer: C

Question #:5

The LED on a MacBook MagSafe power adapter doesn't illuminate at all when it's plugged into the MacBook and you know the adapter is connected to a known good power source. What is most likely the cause of this symptom?

- A. The MacBook has a faulty main battery.
- B. The MagSafe adapter needs to be reset first.
- C. The MacBook requires an SMC firmware update.
- D. A MagSafe adapter connector pin is stuck down.

Answer: D

Question #:6

A MacBook Pro powers on with no image on the built-in display. You connect an external display and restart the MacBook Pro, yet you still see no image on either display. Which of the following is most likely the cause of this symptom?

- A. Dead battery
- B. Not enough RAM
- C. Faulty optical drive
- D. RAM not completely seated

Answer: D

Question #:7

You are about to replace a MacBook Air logic board. Which of the following is the most important step you

should take immediately after removing the bottom case?

- A. Remove the thermal module.
- B. Disconnect the main battery.
- C. Remove the hard drive.
- D. Remove the processor.

Answer: B

Question #:8

To ensure proper fan and temperature control in the Power Mac G5, you must run the thermal calibration routine found on the _____ disc whenever you replace a processor or logic board with a new processor or logic board.

- A. Apple Service Diagnostic
- B. Apple Hardware Test
- C. Fan Control Installer
- D. Mac OS X Installer

Answer: A

Question #:9

What does Apple recommend you do before replacing or installing any internal parts in an Xserve?

- A. Remove all drive modules from the Xserve.
- B. Remove the Xserve from its rack.
- C. Press the System Identifier button.
- D. Unlock all drive module bays.

Answer: B

Question #:10

You are troubleshooting an eMac that has no image on its built-in display. You have already checked user controls and reset PRAM, but the issue persists. When you connect an external display to the eMac's VGA output port and restart the eMac, you see a proper image on the external display. Which of the following service modules would most likely be the cause of these symptoms?

- A. Display Analog Assembly
- B. Power Supply Assembly
- C. Logic Board
- D. Hard drive

Answer: A




About Exams4sure.com

Exams4sure.com was founded in 2007. We provide latest & high quality IT / Business Certification Training Exam Questions, Study Guides, Practice Tests.

We help you pass any IT / Business Certification Exams with 100% Pass Guaranteed or Full Refund. Especially Cisco, CompTIA, Citrix, EMC, HP, Oracle, VMware, Juniper, Check Point, LPI, Nortel, EXIN and so on.

View list of all certification exams: [All vendors](#)



We prepare state-of-the art practice tests for certification exams. You can reach us at any of the email addresses listed below.

- ▶ Sales: sales@exams4sure.com
- ▶ Feedback: feedback@exams4sure.com
- ▶ Support: support@exams4sure.com

Any problems about IT certification or our products, You can write us back and we will get back to you within 24 hours.